


UVC Upper Room Linear Wall Fixture

Directing the power of light to clean indoor air.

SERIES R
UVC Upper Room Linear Wall Fixture
Model SRLW



PRODUCT DESCRIPTION

Utilizing natural air circulation to move contaminated air into the Upper Room Zone, the Upper Room Linear Wall Fixture™ inactivates airborne viruses using the proven power of UVC light¹. And with a minimalistic design that makes it barely noticeable, the focus will be on the air, not the fixture.


SPECIFICATION STATEMENT

Solution shall consist of a UVC Upper Room Fixture that uses 253.7 nm UVC light to inactivate airborne viruses such as SARS-CoV-2. Fixture shall include multiple safety features including PIR sensors, auto-off switch for lamp replacement, and optimized beam control to direct UVC distribution to upper room zone. UVC dosage must be based on SARS-CoV-2 genome modeling with computer-aided computation for specific rooms sizes.

The most complete UVC Upper Room Linear Wall Fixture solution available.

SERIES R

UVC Upper Room Linear Wall Fixture | Model SRLW



FIXTURE

- Dimensions: 48.81" w x 7.88" d x 1.63" h
- Weight: 22 lbs.
- Silent operation
- Easy lamp replacement
- Made in America with U.S. and global components

AIRFLOW

- Single unit designed for an average 400 ft² / 3,600 ft³ space (20' x 20' x 9')
- UVC dosage calculated upon average air flow in a typical room with HVAC

UVC LAMPING

- Philips 40-watt 253.7 nm UVC lamp
- Up to 9,000 hours lamp life at 85% UVC intensity
- No ozone emissions

ELECTRICAL

- 120-277VAC, .33-.14 Amps
- 40 watts
- Hard-wired standard; cord-connect optional

OPERATION

- Suitable for areas where bottom of fixture can be mounted at least 8'10" above finished floor; fixture may be lowered to 8'2" when opposing wall parallel to light source is less than 17' from fixture. See Installation and Operation Manual for additional details.
- PIR auto-off sensors to protect against accidental UVC exposure
- Auto-off switch for lamp replacement
- Louvered design for operation in occupied space
- Complies with IEC 62471 Photobiological Safety of Lamps and Lamp Systems

CERTIFICATIONS

- Certified to UL Standards
- Patent pending

SUPPORT

- 3-year warranty
- Field service
- Technical support

Important Information

The Upper Room Linear Wall Fixture's effectiveness in the deactivation of certain airborne viruses is as described above. Safeology does not warrant or guarantee that the use of the product will protect any user from or prevent infection and/or contamination from viruses, bacteria, protozoa, fungi, illness, or disease. The units are not approved as medical devices by the FDA. As such, the Upper Room Linear Wall Fixture is not used to disinfect medical devices. Safeology shall not be liable for any claim or damage that may arise from or relate to any use of this product outside its intended use or contrary to operation instructions, user manuals or mounting instructions.

Safety Warning

DANGER: UVC lamps must be installed and used in the correct manner. Direct exposure to UVC can be dangerous and result in serious damage to the skin and corneas (eyes). UVC lamps must be installed in the Upper Room Linear Wall Fixture in strict accordance with the requirements stated in the user manual or instructions. Safety switches should never be disabled. Unit should not be operated with the top off or with the filters removed. The Upper Room Linear Wall Fixture must only be sold and installed by professionals.

¹ UVC light has been proven to inactivate various pathogens; the dosage required may vary by pathogen. Visit www.safeology.com for additional information.